

FORM Identifier: F 108 Revision: 03 Page: 1/1	Product specification for inductive components	MAGNETEC GmbH Industriestrasse 7 D-63505 Langenselbold
---	--	---



Client:	MAGNETEC GmbH	Magnetec P/N:	M-294	Magnetec A/N:	12355
Client's P/N:	/	PS Index:	02	PS Revision:	02
Subject:	EMC Wandler			Type:	E

1. Mechanical Outline	
Nominal core dimensions: 40 x 32 x 15 Finished product dimensions: OD \leq 43,1 ID \geq 28,8 H \leq 17,4 [dimensions] = mm	

2. Core data			
Core material:	NANOPERM®	$L_{Fe} = 11,26 \text{ cm}$	$A_{Fe} = 0,48 \text{ cm}^2$
Nominal values:	Permeability level 30.000	@ frequency 10 kHz	@ H peak 3,14 mA/cm

3. Inspection values				
	Measured value	Measurement limits	Frequency	leff x N [mA x turn]
	AL [μH]	10,7 - 21,4	10 kHz	25

4. Core finishing	
Type:	Cased
Marking:	MAGNETEC M-294-02 YM (Y = year / M = month)
Packaging:	24 pcs. per layer; 5 layers per carton box; PU = 120 pcs.

5. Comments:	
	<input checked="" type="checkbox"/> Marking date code (YM) acc. to IEC 62 5.1; YM = production year and month <input checked="" type="checkbox"/> RoHS compliant according to directive 2002/95/EC

Index / Revision	Alteration	Date
01 / 01	Product Specification	18.04.2006
02 / 02	Case material Ultramid; Case height \leq 17,4mm	06.04.2011

Created:	Zs. Eperjesi	Approved (Techn):	F. Záborszky	Approved (Quality):	V. Kaposztas	Released:	F. Rauscher
	06.04.2011		15.04.2011		18.04.2011		26.04.2011