

Overview

Product information

**ESP-200A-50-BK-18-20160000034**

Energy storage Connector, Product range: ESP plug, color: black, Wire cross section: 50 mm², Rated voltage: 1500V, Rated current: 200 A, Connection method: crimped, Contact type: hole type, min. Cable diameter: 12.5mm, Max. Cable diameter: 14mm

Product advantages

- Exclusive patents
- IP67 protection
- With safety locking latch
- The plug can rotate 360° after assembled
- The socket is with hand-proof protection
- With color-coded and mechanism-coded design avoiding misplug

Product certification



Technical data

Product drawing

3D model

□

Wiring data

Cable sectional area	1/0AWG(50mm ²)
Number of connections	1
Cable outer diameter	12.5~14mm
Cable stripping length	13~14mm
Wiring mode	Crimp

Environment condition

Protection grade (pair plug)	IP67
Ambient temperature (operation)	-40°C ~ +125°C
Ambient temperature (storage/transportation)	-40°C ~ +80°C
Altitude	2000m

Mechanical properties

Plugging times	100
Pullout force	>10N

Mechanical properties

Insertion force	< 100N
-----------------	--------

Standards and specifications

Standard/Specification	UL4128
------------------------	--------

Material data

Insulating material	Nylon
Clamping ring material	Silicone
O-ring material	Silicone
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Contact material	Copper alloy
Shell color	Black
Flammability rating	UL94V-0

Electrical parameters

Pollution level	3
Rated current	UL DC1500V
	200A

Insulation resistance	>5000MΩ
Contact resistance	≤0.5mΩ

Accessories

Business data	
Order number	20160000034
Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	67.83