

Product Specifications



Core type:


EQ20/R + PLT20/14/2/S

Selling unit:

PCS


Product dimensions (mm): EQ20/R

	Nom	Tol +	Tol -	Max	Min
A	20.00	0.35	0.35	20.35	19.65
B	14.00	0.30	0.30	14.30	13.70
C	12.86	0.35	0.35	13.21	12.51
D2	18.00	0.35	0.35	18.35	17.65
D3	8.80	0.15	0.15	8.95	8.65
E	6.30	0.10	0.10	6.40	6.20
F	4.10	0.15	0.15	4.25	3.95
G	5.30	0.15	0.15	5.45	5.15
H	2.90	0.10	0.10	3.00	2.80



Product dimensions (mm): PLT20/14/2/S

	Nom	Tol +	Tol -	Max	Min
A	20.00	0.35	0.35	20.35	19.65
B	14.00	0.30	0.30	14.30	13.70
C	2.30	0.05	0.05	2.35	2.25
D	1.90	0.10	0.10	2.00	1.80
E	3.00	0.10	0.10	3.10	2.90



Effective parameters

Effective area	Minimum area	Effective length	Effective volume	Core factor
$A_e = 59.8 \text{ [mm}^2\text{]}$	$A_{min} = 55 \text{ [mm}^2\text{]}$	$L_e = 25.1 \text{ [mm]}$	$V_e = 1500 \text{ [mm}^3\text{]}$	$C_1 = 0.42 \text{ [mm}^{-1}\text{]}$

Inductance factor

Material	Value	Tol +	Tol -	Measuring conditions			Unit
3C95	5660	25%	25%	10 kHz	< 0.1 mT	25°C	nH/turns ²
3C96	4350	25%	25%	10 kHz	< 0.1 mT	25°C	nH/turns ²
3F36	3200	25%	25%	10 kHz	< 0.1 mT	25°C	nH/turns ²
3F46	1900	25%	25%	10 kHz	< 0.1 mT	25°C	nH/turns ²

Power loss

Product Specifications



Core type:

EQ20/R + PLT20/14/2/S

Selling unit:

PCS

Material	Symbol	Value	Measuring conditions			Unit
3C95	Pv	< 0.72	100 kHz	200 mT	100°C	W/set
3C95	Pv	< 0.78	100 kHz	200 mT	25°C	W/set
3C96	Pv	< 0.67	100 kHz	200 mT	100°C	W/set
3C96	Pv	< 0.27	400 kHz	50 mT	100°C	W/set
3F36	Pv	< 0.22	500 kHz	50 mT	100°C	W/set
3F36	Pv	< 1.7	500 kHz	100 mT	100°C	W/set
3F46	Pv	< 0.6	1000 kHz	50 mT	100°C	W/set
3F46	Pv	< 0.32	3000 kHz	10 mT	100°C	W/set

Bsat

Material	Symbol	Value	Measuring conditions			Unit
3C95	Bsat	> 330	10 kHz	250 A/m	100°C	mT
3C96	Bsat	> 340	10 kHz	250 A/m	100°C	mT
3F36	Bsat	> 320	10 kHz	250 A/m	100°C	mT
3F46	Bsat	> 330	10 kHz	250 A/m	100°C	mT

Accessories

Ordering name	Description	Ordering code
CLM-EQ20/PLT20	Clamp	432202104431