

Description



Silicon Carbide (SiC) MOSFET use a completely new technology that provide superior switching performance and higher reliability compared to Silicon. In addition, the low ON resistance and compact chip size ensure low capacitance and gate charge. Consequently, system benefits include highest efficiency, faster operating frequency, increased power density, reduced EMI, and reduced system size.

Features

- High Speed Switching with Low Capacitances
- High Blocking Voltage with Low RDS(on)
- Optimized package with separate driver source pin
- Easy to parallel and simple to drive
- ROHS Compliant, Halogen free

Application

- EV motor drive
- High Voltage DC/DC Converters
- Switch Mode Power Supplies
- Solar inverters
- EV charging



Ordering Information

Part Number	Marking	Package	Packaging
ASC100N1700MT4PB	ASC100N1700MT4	TO-247-4	Tube

Absolute Maximum Ratings(Tc=25°C)

Symbol	Parameter	Value	Unit
V _{DS}	Drain-Source Voltage	1700	V
I _D	Drain Current(continuous)at Tc=25°C	100	A
I _D	Drain Current(continuous)at Tc=100°C	75	A
I _{DM}	Drain Current (pulsed)	200	A
V _{GS}	Gate-Source Voltage	-8/+19	V
P _D	Power Dissipation T _C = 25°C	470	W
T _J , Tstg	Junction and Storage Temperature Range	-55 to +175	°C

Electrical Characteristics(T_J = 25°C unless otherwise specified)

Typical Performance-Static

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
BV _{DS}	Drain-source Breakdown Voltage	I _D =250uA, V _{GS} =0V	1700			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =1700V, V _{GS} =0V, T _J =25°C		5	100	uA
I _{GSS}	Gate-body Leakage Current	V _{DS} =0V ; V _{GS} =-8 to 19V		10	250	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D =20mA	1.8	2.5	3.6	V
V _{GS(on)}	Recommended turn-on Voltage	Static		15		V
V _{GS(off)}	Recommended turn-off Voltage			-4		V
R _{DS(on)}	Static Drain-source On Resistance	V _{GS} =15V, I _D =50A		25	30	mΩ
		V _{GS} =15V, I _D =50A T _J =175°C		42		mΩ

Typical Performance-Dynamic

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input Capacitance	$V_{DS}=1200V, f=1MHz,$ $V_{AC}=25mV$		6465		pF
C_{oss}	Output Capacitance			195		pF
C_{rss}	Reverse Transfer Capacitance			16		pF
g_{fs}	Transconductance	$V_{DS}=20V, I_D=50A$		60		S
E_{OSS}	C_{OSS} Stored Energy	$V_{DS}=1200V, f=1MHz$		109		μJ
E_{ON}	Turn-On Energy (Body Diode)	$V_{DS}=1200V,$ $V_{GS}=-4/15V, I_D=50A,$ $L=150\mu H, T_J=175^\circ C$		0.72		mJ
E_{OFF}	Turn-Off Energy (Body Diode)			0.21		mJ
Q_g	Total Gate Charge	$V_{DS}=1200V,$ $V_{GS}=-4V/15V, I_D=50A,$		166		nC
Q_{gs}	Gate-source Charge			52		nC
Q_{gd}	Gate-Drain Charge			50		nC
$R_{G(int)}$	Internal Gate Resistance	$f=1MHz, V_{AC}=25mV$		3		Ω
$t_{d(on)}$	Turn-on Delay Time	$V_{DS}=1200V,$ $V_{GS}=-4V/15V,$ $I_D=50A, L=150\mu H$ $R_{ext}=2.5\Omega$		32		ns
t_r	Rise Time			36		ns
$t_{d(off)}$	Turn-off Delay Time			62		ns
t_f	Fall Time			15		ns

Typical Performance-Reverse Diode($T_J = 25^\circ C$ unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_{FSD}	Forward Voltage	$V_{GS}=0V, I_F=37.5A, T_J=25^\circ C$		3.2	6	V
		$V_{GS}=0V, I_F=37.5A, T_J=175^\circ C$		2.9	6	V
I_S	Continuous Diode Forward Current	$V_{GS}=0V, T_C=25^\circ C$		100		A
t_{rr}	Reverse Recovery Time	$V_{GS}=-4V, I_F=50A,$ $V_R=1200V, di/dt=1900$ $A/\mu s, T_J=175^\circ C$		32		nS
Q_{rr}	Reverse Recovery Charge			917		nC
I_{rrm}	Peak Reverse Recovery Current			38		A

Thermal Characteristics

Symbol	Parameter	Value.	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	0.32	$^\circ C/W$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	40	$^\circ C/W$

The values are based on the junction-to case thermal impedance which is measured with the device mounted to a large heat sink assuming maximum junction temperature of $T_J(max)=175^\circ C$

Electrical Characteristics

Fig1. Output characteristics ($T_J = 25^\circ\text{C}$)




Fig2. Output characteristics ($T_J = 175^\circ\text{C}$)




Fig3. Normalized On-Resistance vs. Temperature




Fig4. On-Resistance vs. Temperature




Fig5. Transfer Characteristic




Fig6. Body Diode Characteristic at 25°C




Fig7.Threshold Voltage vs. Temperature




Fig8. Gate Charge Characteristics




Fig9. 3rd Quadrant Characteristic at 25 $^{\circ}C$




Fig10. Output Capacitor Stored Energy




Fig11. Capacitances vs. Drain-Source




Fig12. Max Power Dissipation Derating Vs T_c




Fig13. Switching Energy vs. Drain Current




Fig14. Switching Energy vs. $R_{G(ext)}$




Fig15. Switching Energy vs. Temperature




Fig16. Switching Times vs. $R_{G(ext)}$




Fig17. Transient Thermal Impedance






Fig18. Safe Operating Area



Package Drawing:



Dimensions (UNIT: mm)

SYMBDLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	TYPE	MAX	MIN	TYPE	MAX
A	4.80	5.00	5.20	0.189	0.197	0.205
A1	2.85	3.00	3.15	0.112	0.118	0.124
b	1.15	1.20	1.25	0.045	0.047	0.049
b1	2.40	2.50	2.60	0.094	0.098	0.102
b2	2.61	2.76	2.91	0.103	0.109	0.115
b3	1.30	1.42	1.57	0.051	0.056	0.062
C	0.55	0.60	0.65	0.022	0.024	0.026
D	20.80	21.00	21.20	0.819	0.827	0.835
D1	15.94	16.24	16.54	0.628	0.639	0.651
D2	4.3TYPE			0.169TYPE		
e1	4.93	5.08	5.23	0.194	0.200	0.206
e2	2.39	2.54	2.69	0.094	0.100	0.106
E	15.95	16.15	16.35	0.628	0.636	0.644
E1	13.82	14.02	14.26	0.544	0.552	0.561
E2	12.00	12.20	12.40	0.472	0.480	0.488
L	34.65	35.05	35.45	1.364	1.380	1.396
Q	5.85	5.95	6.05	0.230	0.234	0.238
øP	3.45	3.60	3.75	0.136	0.142	0.148
θ	17.5°			0.689°		

Notes:

- The information in this document is subject to change without notice.
- For more product and company information, please contact us or visit the website.

Contact Info:

- Tel: +86 13510099916
- Web: www.ewsemi.com



专注

Focus

品质

Quality

创新

Innovation

共赢

Win-win

