



Расшифровка

| | | | | | | |
|---|----|----|----|--------|------|-------------------------|
| S | 32 | 22 | НС | -E10.3 | -060 | |
| | | | | | | Магнитная проницаемость |
| | | | | | | Высота в мм |
| | | | | | | Конфигурация НС |
| | | | | | | Ширина в мм |
| | | | | | | Длина в мм |
| | | | | | | Материал Sendust |

| Part Number | Dimensions (mm) | | | | | | Path Length (cm) | Cross Section Area (cm ²) | Volume (cm ³) | A _L (nH/N ²)±12% | | |
|---------------|-----------------|------|------|------|------|------|------------------|---------------------------------------|---------------------------|---|------|------|
| | A | B | C | D | E | F | | | | 026μ | 040μ | 060μ |
| S2314НС-E8.7 | 23.4 | 14.0 | 8.7 | 9.2 | 19.4 | 6.2 | 11.8 | 4.91 | 0.670 | 45 | 69 | 103 |
| S2518НС-E8.4 | 25.0 | 18.0 | 8.4 | 11.0 | 21.0 | 5.4 | 17.1 | 4.97 | 0.960 | 63 | 97 | 146 |
| S2518НС-E10.8 | 25.0 | 18.0 | 10.8 | 11.0 | 21.0 | 7.8 | 20.4 | 5.93 | 0.960 | 53 | 81 | 122 |
| S3020НС-E9.2 | 30.0 | 20.0 | 9.2 | 12.0 | 25.6 | 5.9 | 23.7 | 5.81 | 1.140 | 64 | 99 | 148 |
| S3020НС-E11.8 | 30.0 | 20.0 | 11.8 | 12.0 | 25.6 | 8.5 | 27.9 | 6.85 | 1.140 | 54 | 84 | 125 |
| S3222НС-E10.3 | 32.0 | 22.0 | 10.3 | 13.5 | 27.0 | 6.6 | 32.0 | 6.25 | 1.430 | 75 | 115 | 172 |
| S3222НС-E13.4 | 32.0 | 22.0 | 13.4 | 13.5 | 27.0 | 9.7 | 38.2 | 7.49 | 1.430 | 62 | 94 | 144 |
| S3222НС-E15.2 | 32.0 | 22.0 | 15.2 | 13.5 | 27.0 | 11.5 | 42.0 | 8.21 | 1.430 | 57 | 88 | 131 |
| S3624НС-E11.2 | 36.2 | 24.0 | 11.2 | 15.0 | 30.4 | 7.2 | 43.0 | 6.78 | 1.770 | 85 | 131 | 197 |
| S3624НС-E14.4 | 36.2 | 24.0 | 14.4 | 15.0 | 30.4 | 10.4 | 51.1 | 8.06 | 1.770 | 72 | 110 | 166 |
| S4225НС-E12.3 | 42.0 | 25.0 | 12.3 | 16.2 | 35.2 | 7.9 | 56.1 | 7.61 | 2.060 | 88 | 136 | 204 |
| S4225НС-E15.8 | 42.0 | 25.0 | 15.8 | 16.2 | 35.2 | 11.4 | 66.4 | 9.01 | 2.060 | 75 | 115 | 172 |

Графики

