


Overview

Product information

**ESS-150A-35-B/S-BK-18-20160000048**

Energy Storage Connector, Product range: ESS socket, Color: black, Wire cross section: 35 mm², Rated voltage: 1500V, Rated current: 150 A, Connection method: Busbar/Screw, Contact type: needle

Product advantages

- ☒ Exclusive patents
- ☒ IP67 protection
- ☒ With safety locking latch
- ☒ The plug can rotate 360° after assembled
- ☒ The socket is with hand-proof protection
- ☒ With color-coded and mechanism-coded design avoiding misplug

Product certification



Technical data

Product drawing

3D model



Wiring data

Wiring mode

Busbar/Screw

Environment condition

Protection grade (pair plug)

IP67

Ambient temperature (operation)

-40°C ~ +125°C

Ambient temperature (storage/transportation)

-40°C ~ +80°C

Altitude

2000m

Mechanical properties

Plugging times	100
Pullout force	>10N

Mechanical properties

Insertion force	< 100N
-----------------	--------

Standards and specifications

Standard/Specification	UL4128
------------------------	--------

Material data

Insulating material	Nylon
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Sealing ring material	Silicone
Contact material	Copper alloy
Shell color	Black
Flammability rating	UL94V-0

Electrical parameters

Pollution level	3
Rated current	150A
	UL DC1500V
Insulation resistance	>5000MΩ
Contact resistance	≤0.5mΩ

Accessories

Business data

Order number	20160000048
--------------	-------------

Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	47