

## Overview

#### **Product information**



# ESP-150A-35-BK-18-20160000008

Energy storage Connector, Product range: ESP plug, color: black, Wire cross section: 35 mm², Rated voltage: 1500V, Rated current: 150 A, Connection method: crimped, Contact type: hole type, min. Cable diameter: 11mm, Max.

Cable diameter: 12.5 mm

## Product advantages

- ☑ Exclusive patents
- ✓ IP67 protection
- ☑ With safety locking latch
- ☑ The plug can rotate 360° after assembled
- ☑ The socket is with hand-proof protection
- $\ensuremath{\mu}$  With color-coded and mechnism-coded desgin avoiding misplug

Product certification





#### Technical data

Deading	4 4	
Produc	t drawing	ı

3D model

## Wiring data

Cable sectional area	2AWG(35mm²)
Number of connections	1
Cable outer diameter	11~12.5mm
Cable stripping length	13~14mm
Wiring mode	Crimp

## **Environment condition**

Protection grade (pair plug)	IP67	
Ambient temperature (operation)	-40°C ~ +125°C	
Ambient temperature (storage/transportation)	-40°C ~ +80°C	
Altitude	2000m	
Mechanical properties		
Plugging times	100	
Pullout force	>10N	
Mechanical properties		
Insertion force	< 100N	
Standards and specifications		
Standard/Specification	UL4128	
Material data		
Insulating material	Nylon	
Clamping ring material	Silicone	
O-ring material	Silicone	
Halogen-free	Compliance with standards	
Environmental protection matters	REACH/RoHS compliant	
Contact material	Copper alloy	
Shell color	Black	
Flammability rating	UL94V-0	
Electrical parameters		
Pollution level	3	
	150A	
Rated current	UL DC1500V	

Insulation resistance	>5000ΜΩ
Contact resistance	≤0.5mΩ

Access	ories
, 100000	01100

Business data		
Order number	20160000008	
Packing unit	50	
Minimum order quantity	50	
Products weight (without packaging)	67.83	