

Overview

Product information

**ESP-120A-25-BK-00-20160000013**

Energy storage Connector, Product range: ESP plug, color: black, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: crimp, Contact type: hole type, min. Cable diameter: 9 mm, Max. Cable diameter: 10.5 mm

Product advantages

- Exclusive patents
- IP67 protection
- With safety locking latch
- The plug can rotate 360° after assembled
- The socket is with hand-proof protection
- With color-coded and mechanism-coded design avoiding misplug

Product certification



Technical data

Product drawing

3D model

□

Wiring data

Cable sectional area	4AWG(25mm ²)
Number of connections	1
Cable outer diameter	9~10.5mm
Cable stripping length	13~14mm
Wiring mode	Crimp

Environment condition

Protection grade (pair plug)	IP67
Ambient temperature (operation)	-40°C ~ +125°C
Ambient temperature (storage/transportation)	-40°C ~ +80°C
Altitude	2000m

Mechanical properties

Plugging times	100
Insertion force	<60N
Pullout force	>10N

Standards and specifications

Standard/Specification	UL4128
------------------------	--------

Material data

Insulating material	Nylon
Clamping ring material	Silicone
O-ring material	Silicone
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Contact material	Copper alloy
Shell color	Black
Flammability rating	UL94V-0

Electrical parameters

Pollution level	3
Rated current	120A
	UL DC1500V
Insulation resistance	>5000MΩ
Contact resistance	≤0.5mΩ

Accessories

Business data

Order number	20160000013
Packing unit	30
Minimum order quantity	50
Products weight (without packaging)	38