

# DOSEMI

# IGBT

## DG75X12T2

### 1200V/75A IGBT with Diode

### General Description

DOSEMI IGBT Power Discrete provides ultra low conduction loss as well as low switching loss. They are designed for the applications such as general inverters and UPS.


### Features

- Low  $V_{CE(sat)}$  Trench IGBT technology
- 10 $\mu$ s short circuit capability
- Low switching loss
- Maximum junction temperature 175°C
- $V_{CE(sat)}$  with positive temperature coefficient
- Fast & soft reverse recovery anti-parallel FWD
- Lead free package

### Typical Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- Uninterruptible power supply

### Equivalent Circuit Schematic



**Absolute Maximum Ratings**  $T_C=25^{\circ}\text{C}$  unless otherwise noted**IGBT**

Symbol	Description	Values	Unit
$V_{CES}$	Collector-Emitter Voltage	1200	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 20$	V
$I_C$	Collector Current @ $T_C=25^{\circ}\text{C}$	150	A
	@ $T_C=137^{\circ}\text{C}$	75	
$I_{CM}$	Pulsed Collector Current $t_p$ limited by $T_{jmax}$	225	A
$P_D$	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	852	W

**Diode**

Symbol	Description	Values	Unit
$V_{RRM}$	Repetitive Peak Reverse Voltage	1200	V
$I_F$	Diode Continuous Forward Current	75	A
$I_{FM}$	Pulsed Collector Current $t_p$ limited by $T_{jmax}$	225	A

**Discrete**

Symbol	Description	Values	Unit
$T_{jop}$	Operating Junction Temperature	-40 to +175	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range	-55 to +150	$^{\circ}\text{C}$
$T_S$	Soldering Temperature, 1.6mm from case for 10s	260	$^{\circ}\text{C}$

**IGBT Characteristics**  $T_c=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		1.75	2.20	V	
		$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}$		2.00			
		$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=175^\circ\text{C}$		2.20			
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=2.72\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	5.6	6.2	6.8	V	
$I_{CES}$	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			250	$\mu\text{A}$	
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			100	nA	
$R_{Gint}$	Internal Gate Resistance			2.0		$\Omega$	
$C_{ies}$	Input Capacitance	$V_{CE}=25\text{V}, f=100\text{kHz}, V_{GE}=0\text{V}$		6.59		nF	
$C_{res}$	Reverse Transfer Capacitance				0.19		nF
$Q_G$	Gate Charge	$V_{GE}=-15\dots+15\text{V}$		0.49		$\mu\text{C}$	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=75\text{A}, R_G=4.7\Omega, V_{GE}=\pm 15\text{V}, L_S=40\text{nH}, T_j=25^\circ\text{C}$		47		ns	
$t_r$	Rise Time			117		ns	
$t_{d(off)}$	Turn-Off Delay Time			157		ns	
$t_f$	Fall Time			212		ns	
$E_{on}$	Turn-On Switching Loss			9.91		mJ	
$E_{off}$	Turn-Off Switching Loss			4.30		mJ	
$t_{d(on)}$	Turn-On Delay Time		$V_{CC}=600\text{V}, I_C=75\text{A}, R_G=4.7\Omega, V_{GE}=\pm 15\text{V}, L_S=40\text{nH}, T_j=150^\circ\text{C}$		52		ns
$t_r$	Rise Time				109		ns
$t_{d(off)}$	Turn-Off Delay Time				203		ns
$t_f$	Fall Time				314		ns
$E_{on}$	Turn-On Switching Loss			13.0		mJ	
$E_{off}$	Turn-Off Switching Loss			6.39		mJ	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=75\text{A}, R_G=4.7\Omega, V_{GE}=\pm 15\text{V}, L_S=40\text{nH}, T_j=175^\circ\text{C}$			53		ns
$t_r$	Rise Time				110		ns
$t_{d(off)}$	Turn-Off Delay Time				235		ns
$t_f$	Fall Time				324		ns
$E_{on}$	Turn-On Switching Loss			14.8		mJ	
$E_{off}$	Turn-Off Switching Loss			6.67		mJ	
$I_{SC}$	SC Data		$t_p \leq 10\mu\text{s}, V_{GE}=15\text{V}, T_j=175^\circ\text{C}, V_{CC}=800\text{V}, V_{CEM} \leq 1200\text{V}$		300		A

**Diode Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_F$	Diode Forward Voltage	$I_F=75\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		2.15	2.60	V
		$I_F=75\text{A}, V_{GE}=0\text{V}, T_j=150^\circ\text{C}$		2.15		
		$I_F=75\text{A}, V_{GE}=0\text{V}, T_j=175^\circ\text{C}$		2.15		
$t_{rr}$	Diode Reverse Recovery Time	$V_R=600\text{V}, I_F=75\text{A},$ $-di/dt=350\text{A}/\mu\text{s}, V_{GE}=-15\text{V},$ $L_S=40\text{nH},$ $T_j=25^\circ\text{C}$		239		ns
$Q_r$	Recovered Charge			2.87		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			19.5		A
$E_{rec}$	Reverse Recovery Energy			0.76		mJ
$t_{rr}$	Diode Reverse Recovery Time	$V_R=600\text{V}, I_F=75\text{A},$ $-di/dt=400\text{A}/\mu\text{s}, V_{GE}=-15\text{V},$ $L_S=40\text{nH},$ $T_j=150^\circ\text{C}$		451		ns
$Q_r$	Recovered Charge			7.62		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			30.6		A
$E_{rec}$	Reverse Recovery Energy			2.63		mJ
$t_{rr}$	Diode Reverse Recovery Time	$V_R=600\text{V}, I_F=75\text{A},$ $-di/dt=400\text{A}/\mu\text{s}, V_{GE}=-15\text{V},$ $L_S=40\text{nH},$ $T_j=175^\circ\text{C}$		481		ns
$Q_r$	Recovered Charge			8.98		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			33.1		A
$E_{rec}$	Reverse Recovery Energy			3.13		mJ

**Discrete Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
$R_{thJC}$	Junction-to-Case (per IGBT)			0.176	K/W
	Junction-to-Case (per Diode)			0.280	
$R_{thJA}$	Junction-to-Ambient		40		K/W




Fig 1. IGBT-inverter Output Characteristics




Fig 2. IGBT Output Characteristics




Fig 3. IGBT Output Characteristics




Fig 4. IGBT-inverter Transfer Characteristics




Fig 5. IGBT-inverter Switching Loss vs.  $I_C$




Fig 6. IGBT-inverter Switching Loss vs.  $R_G$




Fig 7. IGBT-inverter RBSOA




Fig 8. IGBT-inverter Transient Thermal Impedance




Fig 9. Diode-inverter Forward Characteristics




Fig 10. Diode-inverter Switching Loss vs.  $I_F$




Fig 11. Diode-inverter Switching Loss vs.  $R_G$






Fig 12. Diode-inverter Transient Thermal Impedance

**Circuit Schematic**



**Package Dimensions**

Dimensions in Millimeters





## Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see [www.powersemi.cc](http://www.powersemi.cc)), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.  
Changes of this product data sheet are reserved.