



Clamping force by 27mm ≈40N.

| | | | | | |
|-------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------|-------------------|------------------------------------------|-----------------|
| UN - D1041 | | TOLERANCES UNLESS OTHERWISE STATED | | | |
| | | DIMENSION ± | ANGLE ± | ASSEMBLY NO. | QUANT |
| GENERAL ROUGHN. | UNIT | MATERIAL | | PATTERN NO. | |
| ✓ | mm | Stainless steel SUS301 Wnr.: 1.4310 | | | |
| SCALE | PROJ. EUROP. | TREATMENT | | ORDER NO./ORDERNR | QUANT |
| 5:1 | | Ni flash (thickness 0,5µm), Sn plated (thickness >4 µm). Solderability: IEC 60 068-2-20 Part 2. Test Ta, method 1 | | | |
| CLASS.NO. | | CLI/P-RM14/I-S | | 5 | |
| | | | | 4 | |
| | | | | 3 | |
| | | | | 2 | |
| | | | | 1 | 21.02.2024. |
| NAME F. Lach | | SUPERS. | DATE: 21.02.2024. | Property of FERROXCUBE Polska Sp. z o.o. | PAGE GROUP: 112 |
| FILE NAME: CLI_P-RM14_112_08301.idw | | | | PAGES: / 1 | A4 |

4322 021 08301