

INN100W070A

1. General description

GaN-on-Silicon enhancement mode high-electron-mobility-transistor (HEMT) in Solder Bar WLCSP with 2.50 mm x 1.50 mm package size.

2. Features

- GaN-on-Silicon E-mode HEMT technology
- Very low gate charge
- Ultra-low on resistance
- Very small package size
- Zero reverse recovery charge

3. Applications

- Synchronous rectification
- Class-D audio
- High frequency DC-DC converter
- Communication base station
- Motor driver

4. Key performance parameters

Table 1 Key performance parameters at $T_J = 25\text{ }^\circ\text{C}$

Parameter	Value	Unit
$V_{DS,max}$	100	V
$R_{DS(on),max}$ @ $V_{GS} = 5\text{ V}$	7	m Ω
$Q_{G,typ}$ @ $V_{DS} = 50\text{ V}$	4.5	nC
$I_{DS,Pulse}$	125	A
Q_{OSS} @ $V_{DS} = 50\text{ V}$	25	nC

5. Pin information

Table 2 Pin information

PIN	Pin Description	Pin Function
2,4,6	Source	Power Source
3,5	Drain	Power Drain
1	Gate	Driver Gate

Table 3 Ordering information

Type/Ordering Code	Package	Product Code
INN100W070A	WLCSP 2.50x1.50	J17





Table of contents

1. General description 1

2. Features 1

3. Applications..... 1

4. Key performance parameters..... 1

5. Pin information 1

6. Maximum ratings..... 3

7. Thermal characteristics 4

8. Electric characteristics 5

9. Electric characteristics diagrams 7

10.Package outlines 12

11.Reel information 13

12.Land Pattern 14

13.Revision history 15

6. Maximum ratings

at $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified.

Continuous application of maximum ratings can deteriorate transistor lifetime. For further information, contact Innoscence sales office.

Table 4 Maximum ratings

SYMBOL	PARAMETER	MAX	UNIT
V_{DS}	Drain-to-Source Voltage (Continuous)	100	V
I_D	Continuous current	29	A
	Pulsed ($25\text{ }^\circ\text{C}$, $T_{Pulse} = 100\text{ }\mu\text{s}$)	125	A
V_{GS}	Gate-to-Source Voltage	6	V
	Gate-to-Source Voltage	-4	V
T_J	Operating Temperature	-40 to 150	$^\circ\text{C}$
T_{STG}	Storage Temperature	-40 to 150	$^\circ\text{C}$

7. Thermal characteristics

Table 5 Thermal characteristics

SYMBOL	PARAMETER	TYP	UNIT
$R_{\theta JC}$	Thermal Resistance, Junction to Case	0.62	°C/W
$R_{\theta JB}$	Thermal Resistance, Junction to Board	1.98	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient ¹	62.76	°C/W

Note 1: $R_{\theta JA}$ is determined with the device mounted on one square inch of copper pad, single layer 2 oz copper on FR4 board.

8. Electric characteristics

at $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified.

Table 6 Static characteristics

SYMBOL	PARAMETER	MIN	TYP	MAX	UNIT	TEST CONDITIONS
BV_{DSS}	Drain-to-Source Voltage	100	-	-	V	$V_{GS} = 0\text{ V}, I_D = 600\text{ }\mu\text{A}$
I_{DSS}	Drain Source Leakage	-	1.5	14	μA	$V_{GS} = 0\text{ V}, V_{DS} = 80\text{ V}$
I_{GSS}	Gate-to-Source Forward Leakage(25°C)	-	1	15	μA	$V_{GS} = 5\text{ V}$
	Gate-to-Source Forward Leakage(125°C)	-	50	1000	μA	$V_{GS} = 5\text{ V}$
	Gate-to-Source Reverse Leakage	-	0.1	0.5	μA	$V_{GS} = -4\text{ V}$
$V_{GS(TH)}$	Gate Threshold Voltage	0.8	1.1	2.5	V	$V_{DS} = V_{GS}, I_D = 4.3\text{ mA}$
$R_{DS(on)}$	Drain-Source On-state Resistance	-	5.5	7	$\text{m}\Omega$	$V_{GS} = 5\text{ V}, I_D = 16\text{ A}$
V_{SD}	Source-Drain Forward Voltage	-	1.4	-	V	$I_S = 0.5\text{ A}, V_{GS} = 0\text{ V}$

Table 7 Dynamic characteristics

SYMBOL	PARAMETER	MIN	TYP	MAX	UNIT	TEST CONDITIONS
C _{ISS}	Input Capacitance	-	485	-	pF	V _{GS} = 0 V, V _{DS} = 50 V
C _{OSS}	Output Capacitance	-	220	-		V _{GS} = 0 V, V _{DS} = 50 V
C _{RSS}	Reverse Transfer Capacitance	-	3.5	-		V _{GS} = 0 V, V _{DS} = 50 V
C _{OSS(ER)}	Energy Related C _{OSS}	-	340	-		V _{GS} = 0 V, V _{DS} = 0 V to 50 V
C _{OSS(TR)}	Time Related C _{OSS}	-	500	-		V _{GS} = 0 V, V _{DS} = 0 V to 50 V
R _G	Gate resistance	-	2.1	-	Ω	
Q _G	Total Gate Charge	-	4.5	-	nC	V _{GS} = 5 V, V _{DS} = 0 V to 50 V, I _D = 16 A
Q _{GS}	Gate to Source Charge	-	1	-		V _{GS} = 5 V, V _{DS} = 0 V to 50 V, I _D = 16 A
Q _{GD}	Gate to Drain Charge	-	0.8	-		V _{GS} = 5 V, V _{DS} = 0 V to 50 V, I _D = 16 A
Q _{G(TH)}	Gate Charge at Threshold	-	0.6	-		V _{GS} = 5 V, V _{DS} = 0 V to 50 V, I _D = 16 A
Q _{OSS}	Output Charge	-	25	-		V _{GS} = 0 V, V _{DS} = 0 V to 50 V

9. Electric characteristics diagrams

at $T_J = 25^\circ\text{C}$ unless otherwise specified.





Fig. 5 Normalized On-State Resistance vs. Temp.




Fig. 6 Typical Transfer Characteristics




Fig. 7 Typ. Reverse Drain-Source Characteristics ($V_{GS} \leq 0, T_J = 25^\circ C$)




Fig. 8 Typ. Reverse Drain-Source Characteristics ($V_{GS} \geq 0, T_J = 25^\circ C$)




Fig. 9 Typ. Reverse Drain-Source Characteristics ($V_{GS} \leq 0$, $T_J = 125^\circ\text{C}$)




Fig. 10 Typ. Reverse Drain-Source Characteristics ($V_{GS} \geq 0$, $T_J = 125^\circ\text{C}$)




Fig. 11 Typ. Capacitances Characteristics




Fig. 12 Typ. Gate Charge




Fig. 13 Normalized Threshold Voltage vs. Temp.




Fig. 14 Output Charge




Fig. 15 Output Capacitance Stored Energy




Fig. 16 Power Dissipation




Fig. 17 Safe Operating Area







Fig. 18 Max. Transient Thermal Impedance



10. Package outlines


Package Reference




SYMBOL	MILLIMETER			NOTE
	MIN	NOM	MAX	
A	2.475	2.5	2.525	
B	1.475	1.5	1.525	
C	0.23	0.25	0.27	6X
D	0.805	0.825	0.845	
E	0.28	0.3	0.32	
F	0.7875 BASIC			
G	0.5 BASIC			
H	1.155	1.175	1.195	2X
J	1.33	1.35	1.37	2X
K	0.1	0.12	0.14	
L	0.395	0.43	0.465	

NOTE:

- 1) ALL DIMENSION ARE IN MILLIMETERS.
- 2) BOTTOM VIEW IS SOLDER BAR VIEW.
- 3) COMPLIES WITH JEDEC MO-211.
- 4) DRAWING IS NOT TO SCALE.
- 5) A,B IS PACKAGE SIZE
- 6) BAR COPLANARITY SHALL BE 0.05 MILLIMETERS MAX




Marking Reference:




Row	Description	Example
Row1	Company name	INN
Row2	Product code	XXX
Row3	Lot Code	XXX
Row4		XXX
Row5	Date code	YYWW
Row6	Wafer ID	XX
Row7	Location ID	XXXYYY

11. Reel information




12. Land Pattern

Recommended Land Pattern



SYMBOL	MILLIMETER	NOTE
A	2.50	
B	1.50	
C	0.23	6X
D	0.805	
E	0.28	
F	0.7875	
G	0.50	5X
H	1.155	2X
J	1.33	2X

Recommended Stencil Drawing



SYMBOL	MILLIMETER	NOTE
C	0.23	
C1	0.21	5X
D	0.805	
E	0.28	
F	0.7875	
G	0.50	6X
H	1.155	2X
J	1.33	2X

13. Revision history

Major changes since the last revision

Revision	Date	Description of changes
1.0	2022-12-12	1.0 version setup
1.1	2023-03-21	Update the leakage value in table 6
1.2	2023-12-15	Change product code from J19 to J17
1.3	2024-02-26	Add Stencil Drawing

Important Notice

The information provided in this document is intended as a guide only and shall not in any event be regarded as a guarantee of conditions, characteristics or performance. Innoscence does not assume any liability arising out of the application or use of any product described herein, including but not limited to any personal injury, death, or property or environmental damage. No licenses, patent rights, or any other intellectual property rights is granted or conveyed. Innoscence reserves the right to modify without notice. All rights reserved.