




IGBT Modules

V _{CES}	1200V
I _C	75A

Applications

- High frequency drivers
- Electric welding machine
- Solar inverters
- UPS (Uninterruptible Power Supplies)



Features

- High speed IGBT with Trench technology
- Low switching losses
- High short circuit capability(10us)
- Including ultra fast & soft recovery anti-parallel FWD
- Low inductance package
- Maximum junction temperature 175°C

● IGBT

Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value	Unit
Collector-Emitter Voltage	V _{CES}	V _{GE} =0V, I _C =1mA, T _{vj} =25°C	1200	V
Continuous Collector Current	I _C	T _c =100°C	75	A
Repetitive Peak Collector Current	I _{CRM}	tp=1ms	150	A
Gate-Emitter Voltage	V _{GES}	T _{vj} =25°C	± 20	V
Total Power Dissipation	P _{tot}	T _c =25°C T _{vjmax} =175°C	530	W



MG75HF12TFC1

COMPLIANT
RoHS

Characteristic values

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Gate-emitter Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}$, $I_C=3mA$, $T_{vj}=25^{\circ}C$	5.0	5.8	6.4	V
Collector-Emitter Cut-off Current	I_{CES}	$V_{CE}=1200V$, $V_{GE}=0V$, $T_{vj}=25^{\circ}C$			1.0	mA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=75A$, $V_{GE}=15V$, $T_{vj}=25^{\circ}C$		2.10		V
		$I_C=75A$, $V_{GE}=15V$, $T_{vj}=125^{\circ}C$		2.45		
Input Capacitance	C_{ies}	$V_{CE}=25V$, $V_{GE}=0V$, $f=1MHz$, $T_{vj}=25^{\circ}C$		5.52		nF
Reverse Transfer Capacitance	C_{res}			0.26		nF
Gate-Emitter leakage current	I_{GES}	$V_{CE}=0V$, $V_{GE}=20V$, $T_{vj}=25^{\circ}C$			400	nA
Turn-on Delay Time	$t_{d(on)}$	$I_C=75A$ $V_{CE}=600V$ $V_{GE}=\pm 15V$ $R_{GON}=10\Omega$ $T_{vj}=25^{\circ}C$		300		ns
Rise Time	t_r			64		ns
Turn-off Delay Time	$t_{d(off)}$			325		ns
Fall Time	t_f			80		ns
Energy Dissipation During Turn-on Time	E_{on}			6.4		mJ
Energy Dissipation During Turn-off Time	E_{off}			3.0		mJ
Turn-on Delay Time	$t_{d(on)}$	$I_C=75A$ $V_{CE}=600V$ $V_{GE}=\pm 15V$ $R_{GON}=10\Omega$ $T_{vj}=125^{\circ}C$		310		ns
Rise Time	t_r			68		ns
Turn-off Delay Time	$t_{d(off)}$			355		ns
Fall Time	t_f			90		ns
Energy Dissipation During Turn-on Time	E_{on}			9.3		mJ
Energy Dissipation During Turn-off Time	E_{off}			4.6		mJ
SC Data	I_{sc}	$T_p \leq 10\mu s$, $V_{GE}=15V$, $T_{vj}=150^{\circ}C$, $V_{cc}=600V$, $V_{CEM} \leq 1200V$		420		A



● Diode

Absolute Maximum Ratings

Parameter	Symbol	Conditions	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	$T_{vj}=25^{\circ}\text{C}$	1200	V
Continuous DC Forward Current	I_F		75	A
Repetitive Peak Forward Current	I_{FRM}	$t_p=1\text{ms}$	150	A

Characteristic values

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Forward Voltage	V_F	$I_F=75\text{A}, T_{vj}=25^{\circ}\text{C}$		1.95	2.30	V
		$I_F=75\text{A}, T_{vj}=125^{\circ}\text{C}$		2.05		
Recovered Charge	Q_{rr}	$I_F=75\text{A}$ $V_R=600\text{V}$ $-di_F/dt=1200\text{A/us}$ $T_{vj}=25^{\circ}\text{C}$		4.8		μC
Peak Reverse Recovery Current	I_{rr}			60		A
Reverse Recovery Energy	E_{rec}			3.8		mJ
Recovered Charge	Q_{rr}	$I_F=75\text{A}$ $V_R=600\text{V}$ $-di_F/dt=1200\text{A/us}$ $T_{vj}=125^{\circ}\text{C}$		10.2		μC
Peak Reverse Recovery Current	I_{rr}			77		A
Reverse Recovery Energy	E_{rec}			5.7		mJ











MG75HF12TFC1



COMPLIANT
RoHS

● **Module Characteristics** $T_C=25^{\circ}\text{C}$ unless otherwise specified


Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Isolation voltage	V_{isol}	$t=1\text{min}, f=50\text{Hz}$	2500			V
Maximum Junction Temperature	T_{jmax}				175	$^{\circ}\text{C}$
Operating Junction Temperature	$T_{\text{vj op}}$		-40		150	$^{\circ}\text{C}$
Storage Temperature	T_{stg}		-40		125	$^{\circ}\text{C}$
Thermal Resistance Junction-to Case	$R_{\theta \text{ JC}}$	per IGBT			0.26	K/W
		per Diode			0.42	
Thermal Resistance Case-to Sink	$R_{\theta \text{ CS}}$	Conductive grease applied		0.05		K/W
Module Electrodes Torque	M_t	Recommended(M5)	2.5		5.0	N·m
Module-to-Sink Torque	M_s	Recommended(M6)	3.0		5.0	N·m
Weight of Module	G			150		g







● Circuit Diagram



● Package Outline Information

Dimensions in Millimeters

